

S E A C O N

SEACON PRODUCTS 2016/17

Leaders in Underwater Connector Technology and System Solutions



This brochure contains many of our standard product lines which can be customized for higher pressures, different materials and higher electrical ratings or other parameters. Please contact SEACON for your special order requirements.

ELECTRICAL DRY-MATE PRODUCTS

SEACON's electrical dry-mate connectors are mated in air with the mating interfaces being kept dry and sealed from the external environment. Once properly mated, the connector can be submerged to it's rated depth.



RUBBER MOLDED (XS)

- 4 connector sizes (A, F, G, K)
- Up to 12 contacts
- Up to 20,000 psig (approx.45,000ft/13,700m)
- Up to 600 VDC (on standard cable)
- Up to 300 amps
- Neoprene rubber, Glass Reinforced Epoxy, Stainless Steel, Delrin® (DuPont trademark for Acetal Resin)
- SO cable as standard
- Typical uses; Lights, cameras, swimming pool lighting & ROV's



Please see our RUBBER MOLDED brochure for more details.



GRE (GLASS REINFORCED EPOXY)

- 4 connector sizes
- Up to 36 contacts including coax
- Optic & oil filled available
- Up to 20,000 psig (approx.45,000ft/13,700m)
- Up to 2,800 VDC
- Up to 200 amps
- Glass Reinforced Epoxy, Stainless Steel, Delrin® (DuPont trademark for Acetal Resin)
- Typical uses; Lights, cameras and ROV's



Please see our GRE brochure for more details



CS-MS

- 2 shell sizes (J & K)
- Up to 10 contacts
- Up to 7,000 psig (approx.16,000ft/4,780m) mated or open face
- Insulation resistance >1 Gohms @ 500 VDC
- Dielectric with standing voltage <0.5 mA @ 1,000 VAC
- Up to 13 amps
- Optic & oil filled versions available
- Aluminum, Glass Reinforced Epoxy
- Stainless Steel, Copper Alloy also available
- Typical uses; ROV's, cameras, lights and where size and weight is restricted



Please see our CS-MS brochure for more details



55 & 66 SERIES

- 5 shell sizes (15, 16, 20, 24, 32)
- Up to 24 contacts
- Up to 10,000 psig mated/unmated (approx.22,500ft/7,000m)
- 600 VDC
- 5 to 18 amps (dependent on contact size and cable)
- Oil filled & ethernet versions available
- Higher current/voltages available
- Stainless Steel, Neoprene
- Non metallic PEEK version available
- Typical uses; UWTV, lights & ROV's



Please see our 55 & 66 SERIES brochure for more details



HUMMER

- 3 shell sizes (G, K, L)
- Up to 28 contacts
- Up to 10,000 psig mated (approx.22,500ft/7,000m). Open face by special order.
- 300 VDC
- Up to 2.5 amps
- Ethernet versions available
- Copper Alloy, Glass Reinforced Epoxy, Neoprene Rubber, Delrin® (DuPont Trademark for Acetal Resin)
- Rubber jacketed cable as standard
- Typical uses; Lights, cameras and ROV's



Please see our HUMMER brochure for more details



MINI-CON / Micro MINI-CON

- 17 shell sizes
- Up to 203 contacts including coax (MINI-CON)/up to 26 contacts, no coax (Micro MINI-CON)
- Up to 16,000 psig (approx.36,000ft/10,500m)
- Up to 5,000 VDC (MINI-CON)/300 VDC (Micro MINI-CON)
- Up to 23 amps dependent on cable (MINI-CON)/up to 4 amps (Micro MINI-CON)
- Glass sealed inserts available
- Optics & hybrid available
- Oil filled available
- Ethernet version available
- Stainless Steel, Glass Reinforced Epoxy, Copper Alloy (MINI-CON)
- Titanium, Glass Reinforced Epoxy (Micro MINI-CON)
- Typical uses; Drilling systems, umbilical links & submarines



Please see our MINI-CON / Micro MINI-CON brochure for more details



MSS (METAL SHELL SERIES)

- 8 shell sizes (G, K, L, M, O, P, Q, S)
- Up to 156 contacts including coax
- Glass sealed inserts available
- Optics & hybrid available
- API (American Petroleum Institute) versions available
- Positive keying
- PBOF available
- Up to 20,000 psig (approx.45,000ft/13,700m)
- Up to 600 VDC standard (higher ratings available)
- Up to 300 amps (dependent on cable)
- Stainless Steel, Glass Reinforced Epoxy, Copper Alloy
- Typical uses; Drilling systems, umbilical links for ROV's & submarines



Please see our MSS brochure for more details



GLOBE-CON

- 2 shell sizes (G, K) & currently 3 different contact configurations up to 12#28 contacts
- Up to 12 contacts
- Up to 10,000 psig mated (approx.22,500ft/7,000m)
- 300 VDC
- Up to 2.5 amps
- Wet-mate & ethernet versions available
- Materials suitable for caustic environments
- Stainless Steel, Glass Reinforced Epoxy, Neoprene Rubber, Copper Alloy
- Rubber jacketed cable as standard
- Suitable for use in high vibration applications
- Typical uses; Lights, cameras and ROV's or where size is an issue



Please see our GLOBE-CON brochure for more details



MIL-SPEC

- Military specification and design
- Up to 10,000 psig (approx.22,500ft/7,000m)
- Voltage: contact SEACON for details
- Current: contact SEACON for details
- Stainless Steel, MoneI®
- Typical uses; Defense, energy, security, geophysical and telecommunication applications



Please see our SEACON Phoenix brochure for more details

ELECTRICAL WET-MATE PRODUCTS

Our electrical wet-mate connectors enable the user to make and break connections both on the surface and underwater. Many of these connectors have been used successfully over the years for a variety of applications including underwater cameras, diver communications and ROV systems.



ALL-WET

- Round, split and flat configurations
- Up to 42 contact
- Flat **ALL-WET** water blocked version available
- Up to 20,000 psig (approx.45,000ft/13,700m) for round configurations
- Up to 10,000 psig (approx.22,500ft/7,000m) for split & flat configurations
- Up to 600 VDC (with standard cable)
- Up to 50 amps
- Copper Alloy, Neoprene Rubber, Delrin® (DuPont trademark for Acetal Resin)
- SO cable as standard
- Typical uses; Diver communications, UWTV, lights, ROV's

Please see our **ALL-WET** brochure for more details



SEA-MATE

- Second generation **U-MATE**
- 4 Shell sizes (G, K, L, M)
- Up to 37 contacts
- Oil filled option available
- ROV mateable version available
- Ethernet version available
- Up to 7,500 psig mated & open face (approx.16,900ft/5,200m)
- Up to 600 VDC
- Up to 10 amps/50 amps (for new high power version)
- Stainless Steel, Glass Reinforced Epoxy, Hypalon Rubber, Copper Alloy
- Typical uses; Diver communications, UWTV, lights, ROV's & ship to shore communications

Please see our **SEA-MATE** brochure for more details



WET-CON

Micro WET-CON Micro WET-CON Split

- Round, low profile and split configurations
- Up to 16 contacts
- Water blocked / single pin / metal shell / high power / ethernet options available
- Up to 20,000 psig (approx.45,000ft/13,700m) for **WET-CON**
- Up to 10,000 psig (approx.22,500ft/7,000m) for **Micro** and **Split** versions
- Up to 600 VDC with standard cable
- Up to 19 amps
- Copper Alloy, Neoprene rubber, Delrin® (Dupont trademark for Acetal Resin), SO cable as standard, Rubber jacketed cable as standard for **Micro** and **Split** connectors
- Typical uses; Diver communications, UWTV, lights & ROV's

Please see our **WET-CON / Micro WET-CON / Micro WET-CON Split** brochure for more details



U-MATE

- Still available but superseded by **SEA-MATE**
- 3 Shell sizes (G, K, L)
- Up to 12 contacts
- Up to 5,000 psig mated (approx.11,250ft/3,500m)
- Up to 600 VDC
- Up to 10 amps
- Positive keying
- Stainless Steel, NES 833 engaging nut as standard
- Typical uses; Diver communications, UWTV, lights, ROV's & ship to shore communications

Please see our **U-MATE** catalogue section via our website www.seaconworldwide.com more details

OPTICAL HYBRID DRY-MATE PRODUCTS

As fiber optic communication continues to evolve, the **SEACON** Group are able to offer a comprehensive and extensive range of fiber optic products which are designed and manufactured to meet the specific and varied environmental conditions demanded today.



DRY-MATE FIBER OPTICS

- Single-mode & multi-mode
- Using Standard Connector Ranges:
MINI-CON, MSS, OPTI-CON
- Insertion loss < 1.0dB (or < 0.5dB)
- Up to 20,000 psig (approx.45,000ft/13,700m)
- Glass sealed options available in some connector styles and types
- Typical uses; Sonar & surveillance systems, ROV's/AUV's, BOP monitoring equipment, neutrino detection, stress monitoring, subsea camera systems & downhole applications

Please see our **FIBER OPTIC** brochure for more details



OPTI-CON

- 5 Shell sizes (F=1 Way, G=4 Way, M=8 Way, Q=12 Way, T=20 Way)
- 1, 4, 8, 12 & 20 channels in any electrical or optical configuration, single or multi-mode
- Single way right angle version available
- Up to 7,500 psig (approx.16,900ft/5,200m) dependent on cable, shell material & configuration
- 600 VDC
- 4 amps
- Oil filled hose as standard with molded unit as a cost option
- Stainless Steel
- Typical uses; Cameras, monitoring equipment, sonars, towed arrays and any applications requiring high data transfer rates

Please see our **OPTI-CON** brochure for more details



HP/HT (DOWNHOLE)

- Optical, electrical and hybrid (electro/optic) versions available: 2-channel optical only version
2-channel electrical only version
4-channel hybrid (2 electro/2 optic)
- Up to 10,000 psig (approx.22,500ft/7,000m)
- Up to 600 VAC
- Up to 2.5 amps
- Less than 1 inch in diameter
- Field installable termination
- Maximum optical attenuation: 0.3dB
- Maximum optical back reflection: -50dB
- Inconel 625
- Typical uses; High-pressure and high-temperature applications, Downhole & tree/tubing hanger systems

Please see our **HP/HT** Connectors datasheet SAPL-DS-0090 for more details

ELECTRICAL UNDERWATER MATEABLE PRODUCTS

SEACON's underwater mateable electrical connectors have features that protect the electrical contacts from the external environment. In addition, pressure compensated fluid-filled chambers allow repeated mates/de-mates underwater without servicing.



CM2000

- Simple & unique design features combining superior electrical isolation ensuring high connector reliability
- Stab, diver and ROV configurations
- Individual modular pin & socket contacts
- Oil filled & pressure balanced socket contacts
- No single point failures
- Redundant: O-Rings, Seals, Bladders, Bladder closures
- Standard 4, 7 & 12 contacts
- Other configurations up to 19 contacts
- Up to 10,000 psig (approx.22,500ft/7,000m)
- Up to 3.3kVAC
- Up to 100 amps / 250 amps 3.3kVAC versions
- Titanium, 17-4 PH, Nitronic 50, Inconel®. Others available on request.
- Typical uses; Production control, drilling control, ROV, AUV systems, communications & power

Please see our **CM2000** datasheet SAPL-DS-0061 for more details

Please see our **CM2000** 3.3kVAC datasheet SAPL-DS-0062 for more details

Please see our **CM2000** 3.3kVAC 250 amp datasheet SAPL-DS-0063 for more details

Please see our **CM2001** datasheet SAPL-DS-0080 for more details

OPTICAL UNDERWATER MATEABLE PRODUCTS

Our underwater mateable optical connectors manufactured by SEACON Advanced Products, LLC., of Bellville, Texas, USA include the field proven **HYDRALIGHT** second generation fiber optic connector and the new **G3** third generation connector suitable for downhole applications.



HYDRALIGHT

- 2nd generation, field proven, underwater mateable connector
- 8-channel optic only / UPC & APC versions available
- 8-channel hybrid connector (4 electro / 4 optic) & 48 channel
- Up to 10,000 psig (approx.22,500ft/7,000m)
- Oil filled & pressure balanced
- Qualified for 7,000m
- Average single-mode insertion loss better than 0.2dB (0.5dB max)
- Average single mode back reflection of -50dB over mated cycle life (min -30dB)
- Titanium
- Design life of 30 years
- Typical uses; High speed communications, long-distance, production control, pumping systems, sensing systems, Riser and PRM systems
- Portable Oil-Filled Station available to remove contaminants from the oil prior to filling

Please see our **HYDRALIGHT** datasheet SAPL-DS-0001 for more details

Please see our **HYDRALIGHT-APC** datasheet SAPL-DS-0005 for more details

Please see our **48 CHANNEL HYDRALIGHT** datasheet SAPL-DS-0016 for more details

Please see our **HYBRALIGHT** datasheet SAPL-DS-0018 for more details

Please see our **PORTABLE OIL-FILLED STATION** datasheet SAPL-DS-0512 for more details



G3

- 3rd generation connector utilizing **HYDRALIGHT** technology
- Very small form factor, with low loss optical performance
- Matched pairs not required
- Internal pressure compensated
- Suitable for stab, diver and ROV operations
- 6-channel optic (single-mode, multi-mode)
- Up to 15,000 psig (approx.35,000ft/10,000m)
- Operating temperature 150°C (302°F)
- Few internal moving parts
- Simplicity of operation
- Patented 'Joined Chamber' concept
- Stainless Steel, Titanium
- Typical uses; High speed communications & fiber sensing, long-distance, production control, space-restricted applications, tree/tubing hanger systems, DTS, DPS, DAS systems

Please see our **G3** datasheet SAPL-DS-0030 for more details

OPTICAL & ELECTRICAL PENETRATORS



We manufacture a wide range of penetrators for use in applications in which a waterproof seal needs to be made between a cable and a pressure vessel. This is often accomplished using a connector set, but if there is no requirement to separate the cable from the equipment a penetrator can be used. Typical uses; high speed communications, long-distance, production control.

Please see our **OPTICAL FIBER PENETRATORS** datasheet SAPL-DS-0100 for more details or see our **PENETRATORS** catalog section via our website - www.seaconworldwide.com

FIELD INSTALLABLE PRODUCTS

In recent years the search for oil has required operations in progressively deeper waters by mobile offshore drilling units. Drilling at these depths places strong demands on equipment, particularly the cable and connectors that link subsea operations to the surface. SEACON addressed the equipment problem by developing an underwater connector system with high reliability, improved condition assessment capability and better maintainability. SEACON's next-generation multiplex (MUX) cable termination system is the tangible result of the company's ability to apply real-world operator field experience to its product design and produce a step-change improvement in connector performance.

SEACON's range of MUX systems consist of 1 Atmosphere and Positively Pressurized (RUFF-NEK) connector solutions as well as the new underwater cable termination system which consists of the **ARMOR TERMINATION ASSEMBLY (ATA)**, **BREAKAWAY UNIT** and **RUFF-NEK** connector.

The **RUFF-NEK** connector is an electro/optical/mechanical termination that contains an integral system that does not rely on separate external compensator systems to apply a constant overpressure (internal pressure greater than external pressure) to the end of the cable and termination volume. The overpressure is maintained at 15 pounds per square inch (psi) over ambient pressure and helps to prevent water intrusion into the termination chamber that could be caused by flooding of the conductor strands (in the event of cable jacket and conductor insulation breach) or by seal failure. In the cable termination system the **ATA** is affixed to a clevis mount (padeye) at a convenient location on the BOP (Blow Out Prevention) stack while the **RUFF-NEK** connector mates to either a transformer module, crossover or directly to the subsea electronics module (pod). The orientation aspect that can be a problem with a conventional connector is eliminated due to the breakaway unit that interfaces the **ATA** with the BOP, enabling a connection in 90-degree intervals.

There are many benefits to the cable termination system including a lighter, more manageable connector, separate armor termination function from electrical connector function and a controlled breakaway function.

Every seal is redundant (e.g., dual versus single o-ring) for maximum reliability, and everywhere possible, the seals are testable to enable verification of seal integrity off the critical path. The **RUFF-NEK** connector provides visual verification of correct pressure over ambient. It also includes the ability to electrically check for fluid contamination without opening the connector.

ARMOR TERMINATION ASSEMBLY (ATA)
Please see our **ATA** datasheet SAPL-DS-0302 for more details

BREAKAWAY UNIT
Please see our **BREAKAWAY UNIT** datasheet SAPL-DS-0301 for more details

MSSQ RUFF-NEK CCP
Please see our **MSSQ RUFF-NEK CCP** datasheet SAPL-DS-0341 for more details

SBP SERIES FIELD INSTALLABLE & TESTABLE ASSEMBLY (FITA)
Please see our **SBP SERIES FITA** datasheet SAPL-DS-0361 for more details

FIELD INSTALLABLE & TESTABLE ASSEMBLY (FITA)
Please see our **FITA** datasheet SAPL-DS-0321 for more details

SUBSEA UMBILICAL TERMINATION ASSEMBLY (SUTA)
Please see our **SUTA** datasheet SAPL-DS-0311 for more details

MSSQ FLANGED CONNECTOR RECEPTACLE (FCR)
Please see our **MSSQ FCR** datasheet SAPL-DS-0304 for more details

RIGHT ANGLE FLANGED CONNECTOR RECEPTACLE (FCR)
Please see our **RA-FCR** datasheet SAPL-DS-0303 for more details

ATA FITA Termination System

EXPLOSION PROOF

In recent years there has been an increased requirement for connectors to operate in hazardous environments and many applications now require quick and safe disconnection of connectors to be used in these environments. As a result SEACON has developed a new robust range of EXD connectors.



EX-MATE

- Wet mateable in depths of up to 50m*
- Designed around existing **SEA-MATE** range
- 4 shell sizes (G, K, L, M)
- Up to 37 contact configurations
- Interchangeable inserts
- Rated to IP68
- Incorporates Atex approved glanding system
- Atex certification to II 2G Ex d IIB T6 amb -40°C to + 55°C (certificate number TRAC14ATEX0005X & IECEx TRC14.0003X)
- Suitable for applications including Topside FPSO, Drilling Vessels or any potentially explosive environment as covered by the extensive qualification testing

Please see our **EX-MATE** catalogue section via our website for more details - www.seaconworldwide.com
* Subject to further testing.

DOWNHOLE PRODUCTS

Our range of products for downhole applications include the **HP/HT** connector available in either electrical, optical or hybrid versions and recently developed **G3** 3rd Generation 6-channel optic which combines the strength of the **HYDRALIGHT** design with the latest technology from the telecommunications industry. For further information please see our **DOWNHOLE** catalog section via our website - www.seaconworldwide.com or see the individual datasheets below;

G3



- 3rd generation connector utilizing **HYDRALIGHT** technology
- Very small form factor, with low loss optical performance
- Matched pairs not required
- Internal pressure compensated
- Suitable for stab, diver and ROV operations
- 6-channel optic (single-mode, multi-mode)
- Up to 15,000 psig (approx.35,000ft/10,000m)
- Operating temperature 150°C (302°F)
- Few internal moving parts
- Simplicity of operation
- Patented 'Joined Chamber' concept
- Stainless Steel, Titanium
- Typical uses; High speed communications & fiber sensing, long-distance, production control, space-restricted applications, tree/tubing hanger systems, DTS, DPS, DAS systems

Please see our **G3** datasheet SAPL-DS-0030 for more details

HP/HT (DOWNHOLE)



- Optical, electrical and hybrid (electro/optic) versions available: 2-channel optical only version
2-channel electrical only version
4-channel hybrid (2 electro/2 optic)
- Up to 10,000 psig (approx.22,500ft/7,000m)
- Up to 600 VAC
- Up to 2.5 amps
- Less than 1 inch in diameter
- Field installable termination
- Maximum optical attenuation: 0.3dB
- Maximum optical back reflection: -50dB
- Inconel 625
- Typical uses; High-pressure and high-temperature applications, Downhole & tree/tubing hanger systems

Please see our **HP/HT** Connectors datasheet for more details - SAPL-DS-0090

CM2001



- High integrity, single pin, electrical connector
- Less than 1 inch diameter
- Up to 10,000 psig (approx.22,500ft/7,000m)
- 1,000 VAC
- Up to 10 amps
- Rated to 7,000m
- Oil filled, molded cable, customer specific terminations
- Extensive qualification testing data available
- Titanium, 17-4 PH, Nitronic® 50, others available upon request
- Typical uses; Production control systems, communications, space-restricted applications, Downhole & XT's

Please see our **CM2001** datasheet SAPL-DS-0080 for more details

4 CHANNEL DRY-MATE FIBER OPTIC CONNECTOR



- Small compact connector
- 4-channel optic
- Up to 10,000 psig (approx.22,500ft/7,000m)
- Single-mode or multi-mode fiber accommodated
- Dual "O" seals
- PBOF available
- Field installable (in certain environments)
- Operating temperature -20° to 150°C (-4°F to 300°F)
- Titanium or 17-4 PH. Others available to suit different specification/compatibility requirements
- Typical uses; Downhole applications

Please see our **4 Channel Dry-Mate Fiber Optic Connector** datasheet SCE-DS-0001 for more details

VITON®



- High temperature, small diameter and weight
- 8 electrical contacts
- Up to 20,000 psi (approx.45,000ft/13,700m)
- 600 VDC
- 2.5 amps
- Harsh environment compatible
- Positive external grip for disconnection
- Field installable free halves
- Wet mateable
- Operating temperature +200°C (392°F)
- Body material; DuPont VITON®
- Typical uses; Downhole applications

Please see our **VITON®** datasheet SCE-DS-0009 for more details

ETHERNET PRODUCTS



With ever increasing inquiries for connectors to be used for Ethernet applications and our continuous program of specifying suitable connectors from our standard range for use on these systems, **SEACON** has identified a number of standard connector ranges suitable for Ethernet use. These include;

- **HUMMER:** Dry-mate, up to 1Gbps, up to 100m cable length, 10,000 psi/690 bar
- **Micro WET-CON:** Wet-mate, up to 1Gbps, up to 100m cable length, 10,000 psi/690 bar
- **MINI-CON:** Dry-mate, up to 1Gbps, up to 90m cable length, 16,000 psi/1,200 bar
- **55 SERIES:** Dry-mate, up to 1Gbps, up to 80m cable length, tested to 10,000 psi/690 bar
- **SEA-MATE:** Wet-mate, up to 1Gbps, tested to 10,000 psi/690 bar

The initial examination consisted of mating pairs of each connector range and testing against the requirements for the various Ethernet communications standards with a Validator NT955 high speed certifier. Following these tests, the cable/connector assemblies were subjected to pressure testing and certified under pressure. The above tests are for the first products qualified. Additional testing is on-going on a variety of **SEACON** products for Ethernet use. All **ETHERNET** performances are cable dependent. Please see our **ETHERNET** news bulletin for more details via our website - www.seaconworldwide.com

SPECIALTY PRODUCTS

The SEACON Group has produced many specialty products for customers over the years. These include the VITON® connector developed for a high temperature and high pressure application, cable protection products such as the Universal Joint Bend Restrictor and a range of fiber optics. For further information please see our **SPECIALTY PRODUCTS** catalog section via our website - www.seaconworldwide.com or see the individual datasheets below;



SUTA (SUBSEA UMBILICAL TERMINATION ASSEMBLY)

- Integral Fiber Management System
- High Pressure Fiber Optic Feed through Penetrations
- Dual cone, mechanical armor plug
- Overall boot sealed
- Depth rating: Full Ocean Depth
- Oil filled & pressure compensated
- Compatible with embedded & non-embedded MUX cables
- Field installable (no compounds)
- Options for multiple cable entry/multiple connections

Please see our **SUTA** datasheet SAPL-DS-0311 for more details



UNIVERSAL JOINT BEND RESTRICTOR

- Utilizes a universal joint design that allows cable bending through restricted space areas whilst still providing an adequate level of strain relief & bend restriction
- Suitable for **MSS**, **MINI-CON** & **Micro MINI-CON**
- Operating Tensile Load: 267 kN (60,000 lbf)
- Dynamic Cyclic Bend Load: 50 kN (11,000 lbf)
- Depth Rating: 1,500m (5,000 feet)
- Typical uses; Deepwater applications, small bore modular arrays

Please see our **UNIVERSAL JOINT BEND RESTRICTOR** datasheet SEACON-DS-0001 for more details



BDU (BATTERY DISPLAY UNIT)

- Visual indication providing accurate flow and or pressure metering
- Battery charge level
- Qualified in accordance with ISO 13628-6
- Max depth: 3,000m
- Flow accuracy: 375 bar (higher pressure ratings available)
- Typical uses; ROV mateable connectors or surface mateable connectors

Please see our **BDU** datasheet PSAS-DS-0005 for more details



SUBSEA JUMPER ASSEMBLY & DISTRIBUTION HARNESS

- Fiber management
- Good cable flexibility (typical 5" bend radius)
- Deployment techniques similar to jacketed cable
- Good ROV maneuverability during connector mating
- Easy interface to connector
- Early leak detection; some hoses are designed for over-pressure & may be used to offer visible leak paths
- Double barrier against water ingress
- Temperature & pressure compensated
- Size 8mm, 13mm & 20mm ID (Other sizes available upon request)
- Multi-mode & single-mode available
- Typical uses; Ocean science observatories, towed arrays, drilling systems, production control systems and ROV's

Please see our **SUBSEA JUMPER AND DISTRIBUTION HARNESS** datasheet SAPL-DS-0402 for more details



75 OHM COAX

- Design based around SEACON's MINL-CCP shell size
- Bulkhead has a MINL front end interface with a SEACON 5515-FCR mounting interface
- CCP insert manufactured from molded PEEK with a Stainless Steel shell
- FCR has a glass-to-metal seal insert
- Also available with the bulkhead having the standard MINL mounting interface
- Up to 8,400 psig (approx. 19,000ft/5,900m)
- Up to 3-4 amps
- Suitable for a variety of applications

Please see our **75 OHM COAX** datasheet SCE-DS-0013 for more details

UNDERWATER SWITCH PRODUCTS

Our variety of versatile and robust switches include Limit, Positive Action and Proximity which are available in a range of materials including Titanium, Plastic and Stainless Steel. In addition we also offer a Modular Proximity Switch that has been integrated with the **Micro WET-CON** electrical wet-mate connector. Typical uses; position and limit indication, Hall effect, diver communications, dead-switches, communications. For further information please see our **SWITCHES** catalog section via our website www.seaconworldwide.com or see the individual datasheets below;



LIMIT & PLASTIC LIMIT

- Hermetically sealed
- Up to 6,000 psig (approx. 13,840ft/4,200m)
- Rated for > 50,000 cycles
- Load capacities; 1 & 7 amps
- Single pole, double throw
- Plastic Limit switch; Black Acetal
- Stainless Steel or Titanium
- Non-metal options available

Please see our Limit Switches datasheet SAPL-DS-0020 or our Plastic Limit Switches datasheet SAPL-DS-0203 for more details



PROXIMITY & MODULAR PROXIMITY

- Hermetically sealed
- No o-rings or gaskets
- Up to 6,000 psig (approx. 13,840ft/4,200m)
- Rated for > 50,000 cycles
- Load capacities; 1 & 7 amps
- Standard proximity and hall effect
- Proximity switch meets NAVSEA requirements for part number 5162424-101-11
- Magnet retainer meets NAVSEA requirements for part number 5062424-102-11
- Stainless Steel or Titanium

Please see our Proximity Switches datasheet SAPL-DS-0204 or our Modular Proximity Switches datasheet SAPL-DS-0205 for more details



POSITIVE ACTION

- Hermetically sealed
- Up to 6,000 psig (approx. 13,840ft/4,200m)
- Rated for > 50,000 cycles
- Load capacities; 1 & 7 amps
- Single pole, double throw
- Stainless Steel or Titanium

Please see our Positive Action Switches datasheet for more details - SAPL-DS-0206



NEW SWITCH PRODUCTS NOW AVAILABLE

New switch products now available including Proximity Micro Switch, Bulkhead/Panel Mount Reed Sensor Products & Hall Effect Sensors.

Please see our New Switches Products news bulletin for more details via our website - www.seaconworldwide.com

SEACON

1700 Gillespie Way,
El Cajon, California 92020, USA.
TEL: +1 (619) 562-7071
FAX: +1 (619) 562-9706
E-Mail: seacon@seaconworldwide.com
Website: www.seaconworldwide.com

SEACON US GULF AREA SALES OFFICE

14511 Old Katy Road, Suite 300,
Houston, Texas 77079, USA.
TEL: +1 (281) 599-3509
FAX: +1 (281) 599-3517
E-Mail: gulfcoastsales@seaconworldwide.com
Website: www.seaconworldwide.com

SEACON US EAST COAST SALES OFFICE

15 Gray Lane, Suite 108, Hopkinton Industrial Park,
Ashaway, Rhode Island 02804, USA.
TEL: +1 (401) 637-4952
FAX: +1 (401) 637-4953
E-Mail: eastcoastsales@seaconworldwide.com
Website: www.seaconworldwide.com

SEACON ADVANCED PRODUCTS, LLC

1321 Nelius Road, P.O. Box 767,
Bellville, Texas 77418, USA.
TEL: +1 (979) 865-8846
FAX: +1 (979) 865-8859
E-Mail: sales@seacon-ap.com
Website: www.seacon-ap.com

SEACON BRAZIL

Rua Conde de Bonfim 120 sala 212, Tijuca,
Rio de Janeiro, Brazil, CEP: 20520-053.
TEL: +55 (11) 2103-6262
CELL: +55 (21) 9-7626-6062
E-mail: adalberto.bromberg@te.com
Website: www.seaconworldwide.com

SEACON (europe) LTD

Seacon House, Hewett Road, Gapton Hall Industrial Estate,
Great Yarmouth, Norfolk, NR31 0RB, UK.
TEL: +44 (0) 1493-652733
FAX: +44 (0) 1493-652840
E-Mail: sales@seaconeurope.com
Website: www.seaconeurope.com

SEACON GLOBAL PRODUCTION

Callejon Terrazos #8, Local 2-C, Las Brisas 1ra. Seccion,
Tijuana, B.C., Mexico C.P. 22610.
TEL: +52 (664) 626-2726
FAX: +52 (664) 686-8922
E-Mail: sales@seaconglobal.com
Website: www.seaconglobal.com
Dial from U.S.A. TEL: +1 (619) 308-7901
TOLL FREE: (888) 562-7072
FAX: +1 (619) 308-7900

SEACON PHOENIX

15 Gray Lane, Suite 108, Hopkinton Industrial Park,
Ashaway, Rhode Island 02804, USA.
TEL: +1 (401) 637-4952
FAX: +1 (401) 637-4953
E-Mail: sales@seaconphoenixllc.com
Website: www.seaconphoenix.com

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in SEACON standard sales order form. In addition, SEACON reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2016 SEACON
ALL RIGHTS RESERVED

